

Model: MURRAY ATC-1100

Page: 1 of 3

Field Installation Instructions

INSTALLATION MUST BE PERFORMED BY QUALIFIED SUN SERVICE PERSONNEL ONLY

INSTALLATION OVERVIEW: -

The Installation Procedures listed are for the Murray AK-1100. The unit is shipped as a fully assembled unit, with the exception of the item as listed in the Parts List.

PARTS LIST:

DESCRIPTION	PART NUMBER	QUANTITY
Literature Kit XIC-1100	0119-0320-01	1
VCR Tape, Murray	0552-0980-01	1
GM Adapter	0647-0196-01	1
GM/Ford Adapter, Quick-Disconnect	0647-0197-01	1
90 Degree Adapter	0647-0198-01	1
Large GM Adapter, Quick-Disconnect	0647-0199-01	1
Ford Adapter	0647-0200-01	1
Tool Pouch	0671-1012-01	1
Desiccant Bag/Seal	0671-1018-01	10
Installation Instructions	0692-1954-01	1
Murray Banner	0693-1435-01	1
cap Plug	1374-0111-01	6
Yellow Charge Hose Assembly	3988-0232-01	1
Red Hose Assembly	3988-0233-01	1
Blue Hose Assembly	3988-0234-01	1
Red Hose Assembly, with Hand Valve	3988-0235-01	1
Blue Hose Assembly with Hand Valve	3988-0236-01	1
Tank Power Cable Assembly	6004-0668-01	1
Gauge Set Assembly w/o Hoses	7009-2082-01	1
Reclaim Tank Assembly	7009-2083-01	1

REQUIRED TOOLS: -

Complete Sun Issued Tool Kit Safety Goggles (0001-5005)

USE STANDARD REFRIGERANT HANDLING SAFETY PROCEDURES WHEN PERFORMING THIS PROCEDURE

GAUGE SET ASSEMBLY

- 1. Open the container and remove the unit and allaccessories from the shipping container.
- 2. Inventory all items using the parts list and inspect for damage.
- 3. Attach the YELLOW Charge Hose Assembly (3988-0232-01) to the middle connector on the Gauge Set Assembly (7009-2082-01).
- 4. Attach the opposite end of the YELLOW Charge Hose Assembly to the Intake Fort on the back of the unit.
- 5. Attach the BLUE Hose Assembly (3988-0234-01) to the low pressure side of the Gauge Set Assembly (BLUE handle side).
- 6. Attach the RED Hose Assembly (3988-0233-01) to the high pressure side of the Gauge Set Assembly (RED hardle side).
- 7. Attach the BLUE Hose Assembly with Hand Valve (3988-0236-01) to the BLUE Hose Assembly.
- 8. Attach the RED Hose Assembly with Hand Valve (3988-0235-01) to the RED Hose Assembly.
- NOTE: The hoses that are supplied with #e Hand Valves have an angled fitting with a Schrader Valve depressor on one end, and a straight fitting with no depressor on the other end. The straight fittings on the hoses are attached to the Hand Valve and the fitting with the depressor will attach to the Vehicle that is to be serviced.

RECLAIM TANK

- 9. Remove the Reclaim Tank Assembly (7009-2083-01) from the packing container.
- 10. Open the LIQUID Valve on the Tank **Assembly to** relieve any pressure that may be left in the tank.
- 11. Secure the Reclaim Tank Assembly on the **bottom** shelf **by** using the velcro **strap**.
- 12. Connect the **BLUE** Hose Assembly that **is** attached to the Gauge Set Assembly to the port marked LIQUID.
- 13. Ensure that the **VAPOR** Valve is closed.
- 14. Ensure that the LIQUID Valve is open.
- 15. Open the Hand Valve on the BLUE Hose Assembly.

Page 3 of 3

- 16. Open the BLUE Valve on the Gauge Set Assembly.
- 17. close the REX) Valve on the Gauge Set Assembly.
- 18. Ensure that the RED Hand Valve is closed .

NOTE: Ensure all unit switches are in the OFF position.

- 19. Plug in the unit to a grounded AC receptacle.
- 20. Turn the Power Switch to "ON".
- 21. Place the RECLAIM/VACUUM switch to the "VACUUM" position.
- 22. Allow the unit to run until the low pressure gauge reads a vacuum of 24" to 29" for fifteen (15) minutes.
- 23. Turn all switches to the "OFF" position.
- 24. **Close** hand valve on the **end** of the **BLUE** Hose, then close valve on Reclaim Tank.
- 25. Disconnect the BLUE Hose from the tank.

FINAL ASSEMBLY

- 26. Attach the BLUE Hose that **extends** through the left leg of the unit to the LIQUID Port on the Reclaim **Tank** Assembly.
- 27. Attach the **RED** Hose **from** the Left **Leg** Vapor **Port to** the **VAPOR** Port on the Reclaim **Tank** Assembly.
- 28. Open both Tank Valves.
- 29. Place Tool Pouch (0671-1012-01) over the handle and secure with velcro.
- 30. Store all accessories in the tool pouch.
- 31. Complete the questionnaire (0692-1834-01).

CHECKOUT PROCEDURE: ——

Refer **to** Operator's Manual **in** the Literature Kit (0119-0320-01) and the Video **Tape** (0552-0980-01) for Checkout and **Customer** Training **procedures**.