



Model EEWHT8010TR

Truck tire changer for wheels with steel or light alloy rims

- The compact sizes allow to save space and an easy installation on service vehicles.
- The unique centering system of the rim allows quick and safe clamping.
- Control unit with ergonomic design and without cables.
- Equipped with two exclusive 3-piece nylon rollers for safe and quick mount and demount of all tubeless truck tires.

Rim centering capacity	16"-22.5"
Max wheel diameter	mm 1200 (47")
Max wheel width	mm 500 (19.5")
Chuck motor, 3ph, 2 speed	kW ,75 (1 HP)
Hydraulic pump motor, 3ph	kW ,75 (1 HP)
Max torque	Nm 1800 (1320 ft x lbs)
Weight	Kg 330 (726 lbs)
Maximum Height	43 ½"
Maximum Width	60"
Maximum Depth	60"
Voltage	220V / 1ph / 50/60 hz / 30A
Standard Accessories	
Part Number 0001418	Bead Lifting Tool
Part Number 4021100	Star Flange for rims with center holes 220 cm (8.66") and 280 cm (11.02")
Part Number 4021101	Centering Flange (Used with 4021100)
Part Number 021053	Wing Nut
Part Number 4009472	Mounting Clamp
Optional Accessories	
Part Number 4021852	Mounting Clamp for Light Alloy Wheels
Part Number 4021247	Centering Cone and Flange (Center holes 135 – 167 mm) (5.31" – 6.57")
Part Number 4020798	Star Flange for rims with center holes 164 mm (6.46")