



## EEWHT8026 Truck Tire Changer For Tubeless and Tube Type Wheels 14" to 26"

- Oversized chuck shaft creates durability and strength.
- High efficiency transmission increases life of components.
- Quick-fit aluminum protectors and permanent vertical plastic protectors on jaws prevent accidental damage to aluminum rims.
- Quick lock system for mount/demount tool allows faster operation.
- Steel bead breaker disc mounted on nitrogen hardened bushing is easy to lubricate and insures extended life compared to other units with bearings.
- The eight-position switch allows operation of two controls simultaneously.
- Emergency stop-switch complies with latest safety regulations.
- Shut-off switch on chuck arm prevents injury to personnel or other objects laying on its pad.
- Circuit breaker prevents damage caused by short circuits.
- Tool holder carriage mounted on adjustable low-friction synthetic pads gives more power for bead-breaking and allows tolerance of carriage movement to be zeroed.

### Specifications

Rim centering capacity	14"-26"
Max wheel diameter	mm 1500 (59")
Max wheel width	mm 700 (27"1/2)
Bead breaker force	kN 27 (5940 lbs)
Chuck motor, 3ph, 2 speed	kW 1,8 (2,5 HP)
Hydraulic pump motor, 3ph	kW 1,5 (2,0 HP)
Max torque	Nm 1500 (1100 ft x lbs)
Weight	Kg 550 (1210 lbs)
Maximum Width	2000 mm (79")
Maximum Depth	1660 mm (66")
Maximum Height	1200 mm (47")
Voltage	220V / 3ph / 50-60 hz / 15A
<b>Standard Accessories</b>	
Part Number 4004461	Long Tire Tool
Part Number 4014914	Protector for alloy rims
Part Number 4009472	Mounting Clamp
<b>Optional Accessories</b>	
Part Number 4021852	Mounting Clamp for light alloy rims
Part Number 0001418	Short Tire Tool