

TWO-POST GENERAL PURPOSE LIFTS

15K



EELR739A

Shown with standard adapters



15K



LIFTING HEAVY LOADS ARE MADE EASIER WITH THE HOFMANN® 15K TWO-POST LIFT

The 15k Two-Post lift features low profile arms, single point air actuated lock release, over sized steel pulleys, 60" lifting carriage, padded overhead shut-off bar and adapter accessories. Standard height and extended height models available.

SINGLE POINT LOCK RELEASE

- Single point, air actuated lock release allows the technician to disengage both of the columns simultaneously

OVERSIZED STEEL PULLEY SYSTEM

- Oversized, steel pulleys reduce the stress on the equalization system and provide increased durability

LIFTING CARRIAGE

- 60" (152.4 cm) lifting carriage lessens stress on the column by dispersing the load

SCREW PADS

- Standard combination stack screw pads and storage brackets accommodate the technician with a wide range of vehicle pick-up points

OVERHEAD SHUT OFF

- The padded overhead shut off system prevents vehicle damage from being raised too high

ANSI/ALI ALCTV:2011

- Independently Tested and Validated, ALI Certified to the current Automotive lift standard

AVAILABLE MODELS

15K Two-Post (Standard Height)	EELR739A
15K Two-Post (Extended Height)	EELR740A

TECHNICAL SPECIFICATIONS

Capacity	15,000 lbs (6,803 kg)
Rise height*	85" (216 cm)
Overall height	EELR739A: 174" (442 cm) EELR740A: 198" (502.9 cm)
Overall width	154.75" (393.1 cm)
Drive thru width	104.25" (264.8 cm)
Floor to overhead shut off	EELR739A: 167" (424.2 cm) EELR740A: 191" (485.1 cm)
Front and Rear arm reach	38.5" - 62" (97.8 - 157.5 cm)
Screw pad height	6.625" - 8" (16.8 - 20.3 cm)
Inside column width	119.875" (304.5 cm)
Ceiling height requirement	EELR739A: 176" (447 cm) EELR740A: 200" (508 cm)
Rise time	60 Seconds
Power requirements**	208-230V 1Ph 60Hz
Max load per arm	3,750 lbs (1.701 kg)

STANDARD ACCESSORIES

Four u-shaped frame truck adapters	Organizer rack for stack adapter extensions
Four reducer bushings for use with u-shaped frame truck adapters	Four medium and two extended height adapters; 4" (10.1cm) and 8" (20.3cm)

OPTIONAL ACCESSORIES

Air/Electric workstation with filter/lubrications/regulator	EAK0299T27A
24" (61 cm) Height extension†	EAK0299T48A

*Rise height is measured with high extension

**Optional three phase electrical also available, specify at time of order

†Only available for EELR739A

For more information regarding the 15K Two-Post Lift, call 800.251.4500 (US) or 501.505.2662 (Canada) www.hofmann-usa.com / www.hofmann.ca

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2016 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 05/16 SS143422A

