9k varioliftTM

AUTOMOTIVE DOUBLE-SCISSOR LIFT SYSTEM

General purpose, low profile scissor lift designed to accomodate a wide range of vehicles

TITLE





OPTIONAL ACCESSORIES

- Low-profile drive over height of 5.3"
- Lifts straight up no fore or aft movement
- Open front and rear with no crossmember for maximum accessibility
- Dual hydraulic synchronization
- 18 mechanical locking positions with air-actuated release
- Non-slip textured lifting pad surface
- Extendible lifting pad, from 61.25" to 81.5"
- Surface-mount or flush-mount configurations
- ALI/ETL Certified to current ANSI ALCTV lift standard
- For best performance and maximum versatility to service the widest range of vehicles, all surface-mount installed lifts should be installed with the platforms at 23" apart and with the SOET9000LW kit
- SOET9000LW kit includes; long drive over ramps for low-clearance vehicles, outriggers for increased drive over for wider vehicles and additional SOE-VZ975074 connectable rubber blocks. Overall length with kit is 165"
- SOET9000FM lifts should be ordered with SOE-VZ970052 hose extension kit and SOE-VZ970133 foundation insert plates





SOET9000 9k Double-Scissor XL Automotive Lift

SPECIFICATIONS

Equipment Specifications

- Lifting capacity: 9,000 lbs
- Surface-Mount maximum lifting height: 79.75"
- Flush-Mount maximum lifting height: 74.5"
- Surface-Mount lowered height: 5.3"
- Flush-Mount lowered height: 0.0"
- Lifting pad width: <u>25.5</u>"
- Surface-Mount with SOET9000LW overall width: 87.75"
- Flush-Mount overall width: 89"
- Surface-Mount lift length with SOET9000LW: 165"
- Flush-Mount lift length: 83.4"
- Lifting time (with full load):
 53 Seconds
- Lift shipping weight: 2,700 lbs
- SOET9000LW shipping weight: 650 lbs
- Air supply requirements: 90 PSI
- Power requirements: 230V 1Ph 60Hz

*Overall width can be adjusted narrower on installation

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this brochure may change without notice. °2014 Snap-on Incorporated. Hofmann is a trademark of Snap-on Incorporated. All right reserved. 10/14 SS3192A

Hofmann US 309 Exchange Avenue Conway, AR 72032 800.362.4618

Int: 501.505.2739

www.hofmann-usa.com

Hofman Canada 6500 Millcreek Dr Mississauga ON L5N 2W6 800.362.4608 www.hofmann.ca

