

HOFMANN®



201 TrueCut

BRAKE LATHE

201 TrueCut

The Hofmann 201 TrueCut single-speed combination bench brake lathe is designed to handle all your brake resurfacing needs. The 201 Truecut comes equipped with our standard tooling package to resurface most passenger cars & light trucks, optional tooling is available to handle specialty and heavy-duty applications.

Simple "One-Cut" Finish

Feed carriage speed is factory set for a "Like New" micro-finish.

Fast Changeover Of Tooling

Changeover from disc cutter to drum cutter is achieved quickly by swiveling the feed carriage assembly.

Heavy-Duty Construction

From the oversized tapered roller bearings supporting the brake lathe's arbor to the 350 lbs. ductile iron chassis, the 201 TrueCut brake lathe is built for years of machining.

Innovative Tooling Design

The 201 TrueCut standard tooling package is easily adapted to all existing and future machining applications.

Complete Tooling Packing Included

Bearing adapters, cones, rotor and drum silencers, drum and rotor cutter tools, work lamp, drum and rotor hubless cups, wrenches, etc.

Hofmann manufactures a complete line of wheel service equipment.



Imaging & Conventional Alignment Equipment



Tire Changers Designed to Service All Automotive Tires



Scissor and 4-Post Alignment Lifts

HOFMANN[®]
USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com

BRAKE LATHE

Specifications

Rotor/Flywheel/Drum Feed Rate (Per Revolution):	0.0025"
Rotor/Flywheel Diameter Range:	5" - 18"
Maximum Rotor/Flywheel Thickness Range:	3"
Rotor/Flywheel Facing Travel:	4"
Drum Feed Rate Per Revolution:	0.0012" - 0.0120"
Drum Diameter Range:	Up to 14"
Drum Facing Width:	4"
Arbor Speeds:	185 - 190 rpm
Bearing Adapter Range (Standard):	1.285" - 2.781"
Cone Range (Standard):	1.15" - 4"
Maximum Arbor Weight (Standard):	150 lbs.
Drive Motor:	1HP - 1,725 rpm
Drum/Rotor Carriage Motor:	1 Gear Motor
Shipping Weight:	350 lbs.
Power Requirements:	115V, 1Ph, 60 Hz

Standard Accessories

BDL251-1	Lamp
401ST	Tooling kit for passenger car & light truck
CL538	1" Arbor (10.5" Long)
CL605A	Rotor cutting tool
CL771A	Drum cutting tool

Optional Accessories

B206	Heavy-duty bench
B203	Backboard
W177	Foreign car 1/8" arbor kit
TK4-1	Heavy-duty adapter set for 3/4 and 1 ton
W139	Carbide bits (10 each)
1103	Replacement rotor stabilizer (2 each)
108950	Universal hubless adapter set
108963	Universal hubless/composite adapter set
CL503B	Rotor stabilizer

HOFMANN[®]
Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca