HOFMANN®





monty[™] 1520

TIRE CHANGER

monty[™] **1520**

The monty 1520 entry-level tire changer is designed with all the features and durability associated with the Hofmann brand at an affordable price. The monty 1520 features dual clamping cylinders that assure proper clamping power at all four jaws. The monty 1520 handles tires with up to 20" in wheel clamping diameter.

Powerful Two-Stage Bead Breaker

6,000 lbs. of breaking power and a range of up to 13" wide, the monty 1520 can handle the toughest tires.

Dual Wheel Clamping Cylinders

Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheels due to slippage.

Upgradeable

EasyMont Pro features a three-piece design with a Top Roller, Pressing Foot, and Lifting Disc. Each piece provides a specialized function that assists a single operator in mounting/demounting low-profile and high-performance tires.

Powerful Tire Inflation System

Powerful air blast operated by the foot pedal. Each moveable jaw is precisely set to the exact position under the wheel to seal the tire bead.

Four-Jaw Clamping Chuck

Self-centering clamping jaw set clamps wheels up to 20" in diameter from the inside and up to 18" from the outside (22" using optional jaw extensions).

Hofmann manufactures a complete line of wheel service equipment.



Combination brake lathes for rotors, drums and flywheels



Portable Imaging Alignment Systems

TIRE CHANGER

Specifications

Overall Wheel Clamping Diameter:	10" - 20"
Inner-Wheel Clamping Diameter:	12" - 20"
Outer-Wheel Clamping Diameter:	10" - 18"
Bead Breaker Range:	2" - 13"
Bead Loosening Power:	6,000 lbs.
Maximum Wheel Width:	13"
Maximum Outer Tire Diameter:	40"
Shipping Weight:	480 lbs.
Power Requirements*:	120V, 1Ph, 60Hz

Drive Motor/Air Supply Options

Electric (standard) 1HP

Optional Accessories

EAA0329G35A	EasyMont Pro bead assist device
ST4029446	Automotive adapters
	(22" outer clamping diameter)
ST4028566	Motorcycle adapters
	(12" - 21" outer clamping diameter)
EAA0332G84A	ATV adapters
	(7" - 14" outer clamping diameter)
4028228	Quick change bead head kit
EAA0247G20A	Composite mount/demount head
EAA0247G04A	Protective cover (for tire lever)
EAA0304G20A	Outside clamping jaw protectors (4 each)
ST0022129	Snap-in jaw protector
EAA0304G15A	Protective cover for bead breaker shovel
ST4026853	Rim protector, snaps onto rim of wheel
	(3 each - use with wave tire tool)
EAA0247G15A	Protective insert for mount/demount head
	(10 each)
ST0024335	Replacement composite head
EAA0304G14A Wave to	
ST4028648	Magic bead pusher (use with EasyMont)
EAA0332G32A	Round bar with roller attachment (35mm)*
	(Use with EasyMont)
EAA0329G92A	Hex bar with roller attachment
	(Use with EasyMont)
EAA0304G43A	Bead breaker disc (Use with hex bar)
EAA0247G70A	Bead clamp for performance wheels
ST4024078	Bead clamp for run-flat tires
1970995	Premium tire paste

HOFMANN®

USA

309 Exchange Avenue • Conway, AR 72032 (800) 251-4500 • (501) 505-2662 Fax (501) 450-2085 • www.hofmann-usa.com

Canada

6500 Millcreek Drive . Mississauga, ONT L5N 2W6 (800) 267-2185 Fax (905) 821-2073 • www.hofmann.ca