

MOTORCYCLE TIRE CHANGER

monty<sup>®</sup>

TIRE CHANGING SYSTEMS

1520M



HOFMANN<sup>®</sup> 



## MONTY® 1520M/1520EMX TIRE CHANGERS

The Hofmann® *monty* 1520m and 1520emx can handle motorcycle and ATV tires with a maximum wheel width of 13" and wheel clamping diameter from 10" to 21". Optional ATV clamping jaws allow for clamping down to 7". Both tire changers are equipped with standard clamping jaws that allow for changing automotive and light truck tires as well.

### FOUR JAW CLAMPING CHUCK

- These self-centering clamping jaws powered by two pneumatic cylinders allow for tight clamping of motorcycle wheels

### POWERFUL BEAD BREAKER

- 5,954 lbs of breaking power and a range of up to 12" wide, the *monty* 1520m/1520emx provides quick and safe loosening of even tough ATV tire beads

### DUAL WHEEL CLAMPING CYLINDERS

- Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheels due to slippage

### UPGRADEABLE

- EasyMont Pro\* features a three piece design with a top roller, pressing foot and lifting disc. Each piece provides a specialized function that assists a single operator in mounting/demounting low-profile and high-performance tires

### INNOVATIVE DESIGN

- The *monty* 1520m is designed to change all types of motorcycle tires, including tires on the difficult Harley Davidson belt drive wheels. Standard clamping jaws allow for changing automotive and light truck tires as well

### SPECIALLY DESIGNED CLAMPING JAWS

- These clamping jaws are designed to eliminate the additional labor involved in removing the brake disc, sprocket or drive pulley when servicing a wheel. The *monty* 1520m is equipped with plastic protection over metal jaws to protect wheels from damage. Plastic protection is also provided in the bead tool head

\*Standard with *monty* 1520emx, optional with *monty* 1520m

### TECHNICAL SPECIFICATIONS

Part numbers	m1520emx110a m1520m110
Wheel clamping diameter	10" - 21" (25 - 53 cm)
Maximum tire diameter	40" (102 cm)
Maximum wheel width	13" (33 cm)
Compressed air supply	100 - 170 PSI @ 5 CFM
Bead breaking range	0" - 12" (0 - 30.5 cm)
Bead loosening power	5,954 lbs (2,700 kg)
Dimensions (D x W x H)	72" x 68" x 85" (183 x 173 x 2.16 cm)
Shipping weight	419 lbs (190 kg)
Power requirements	120V 1Ph 60Hz

### DRIVE MOTOR/AIR SUPPLY OPTIONS

Electric (standard)	1 HP
Air (available on request)	110 - 170 PSI @ 14 CFM

### STANDARD ACCESSORIES

Tire lever	Lube bottle/swab
Protective insert/roller	Motorcycle jaws

### OPTIONAL ACCESSORIES

EasyMont bead assist device*	EAA0329G35A
Mounting adapter kit*	4027351
Automotive adapters	ST4029446
ATV adapters	EAA0332G84A
Composite mount/demount head	EAA0247G20A
Tire lever protective cover	EAA0247G04A
Protective insert	EAA0247G15A
Wave tire tool	EAA0304G14A
Bead clamp for performance wheels	EAA0247G70A
Premium tire paste	RTT75N

For more information regarding the *monty*® 1520m & 1520emx, call 800.251.4500 (US) or 501.505.2662 (Canada)  
www.hofmann-usa.com / www.hofmann.ca

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet page may change without notice. ©2016 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.  
10/16 SS2712D