

PREMIUM TIRE CHANGERS

MONTY™ 8600





MONTY 8600 LEVERLESS TIRE CHANGER

Leverless demounting and powered wheel lift reduces technician fatigue and opportunity for injury. Dual disc bead breakers are servo positioned and electronically synchronized so the technician can efficiently maintain a safe and ergonomic body position.

WHEEL LIFT

- Reduces fatigue and the chance for injury presented by handling heavy tires and rims

WHEEL CENTER PILOT HOLE CLAMPING

- Center piloting eliminates rim edge damage and provides positive center hole clamping using a cone and quick nut

LASER POSITIONED TOOLING

- Precise rim edge positioning prevents damage to the wheel or tire due to misaligned tool

ERGONOMIC DUAL BEAD BREAKERS

- Easily positioned upper bead breaker and servo driven lower bead breaker. Lower bead breaker is automatically positioned via the upper bead breaker position

LEVERLESS DEMOUNT HEAD

- Integrated demounting finger gently pulls the bead over the rim edge, reducing the possibility of tire or wheel damage

BEAD ASSIST

- Follows the rotation to position the bead in the wheel's drop center on difficult, stiff side wall, tires

INTEGRATED TIRE INFLATION SYSTEM

- Quick and safe top side bead seating and inflation included

STORAGE COMPARTMENT

- Easy access for tools and accessories

QUICK FIT CENTER WHEEL CLAMPING

- Center wheel clamping provides easy and precise wheel mounting while avoiding damage

TECHNICAL SPECIFICATIONS

| | |
|------------------------|-------------------------------------|
| Part number | EEWH742AHNA |
| Wheel diameter | 12" - 30" (30.5 - 76cm) |
| Maximum wheel width | 15" (38cm) |
| Maximum tire diameter | 47" (119cm) |
| Maximum tire weight | 154 lbs (70kg) |
| Mounting speeds | 7/14 RPM CW & 7 RPM CCWM |
| Bead breaker range | 28" (71cm) |
| Bead breaker stroke | 11" (28cm) |
| Bead breaker force | 2,585 lbs (1,173kg) |
| Maximum torque | 1,106 ft*lbs |
| Dimensions (D x W x H) | 70" x 89" x 59" (178 x 226 x 150cm) |
| Noise level | <70dB |
| Shipping weight | 946 lbs (429kg) |
| Compressed air supply | 110 - 140 PSI (7.5 - 9.6 BAR) |
| Power requirements | 200-240V 1Ph 50/60Hz |

STANDARD ACCESSORIES

| | |
|------------------------|--------------------------|
| Quick-clamping nut | Clamping shaft |
| 2.52" cone | 3.07" cone |
| 4.72" cone | 5.70" cone |
| Bead clamp | Magic bead pusher |
| Plastic tire protector | Plastic wheel protectors |
| Lube brush | Tool for bead extraction |
| Rim protection disc | |

OPTIONAL ACCESSORIES

| | |
|---------------------------|-------------|
| Reverse mounted wheel kit | EAA0364G00A |
| Closed center wheel kit | EAA0350G60A |
| Light truck wheel kit | EAA0349G06A |

For more information regarding the monty™ 8600, call 800.251.4500 (US) or 501.505.2662 (Canada) www.hofmann-usa.com / www.hofmann.ca

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2015 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 10/15 SS3308B