

# HOFMANN®



***monty® 2800b***

**TIRE CHANGER**

### Impact Resistant Rotationally Molded Top Cover

- Will handle the high volume requirements of tire service shops
- Recess mounted air gauge for longer life
- Integrated tool storage compartments where they should be...at the work site. Store weight hammers, valve pullers, tire repair accessories within easy reach
- Easy access, externally mounted lube bottle
- Separate integrated valve core tray

### Patented Bead Breakers

- Versatility & wheel protection
- The friction lock on the upper bead breaker ensures breaking the toughest bead without touching the wheel

### Dual Power and Six Second Cycle Time

- Fast & effortless
- Two large air over oil cylinders provide maximum power and operator control both forward and reverse, to handle almost any tire. With the bi-directional combination tool, you can completely demount/mount a tire with only two cycles



monty® 2800b  
Tire Changer

### SPECIFICATIONS

- Rim Diameter: 10.0 - 17.5" (254 - 445mm)
- Rim Width: 3.0 - 19.75" (76 502mm)
- Air Supply Requirement:  
120 - 180 PSI (8 - 12 BAR) @ 5cfm
- Center Post Torque:  
550 ft lbs @ 150PSI (10 BAR)
- Cylinders:  
Two 7" Diameter x 6.5" Stroke  
(177.8mm x 165.1mm)
- Surge Tank:  
10" Diameter x 18.75" High (254mm x 476mm)
- Two-Way Power: Air / Hydraulic
- Shipping Volume: 39 cu ft (1.1 cu m)
- Shipping Weight: 520 lbs (236kg)
- Physical Size: 22" x 54.5" x 44"  
(559mm x 1,384mm x 1,118mm)

### STANDARD ACCESSORIES

- Combination mount/demount tool: 66679
- Tool tray: 66712
- Hold down cone: 66667
- Nylon boot protectors: 66002
- Lube bottle: 66006
- Lube applicator: 1267267