

10K TWO-POST AUTOMOTIVE LIFT

Industrial
Strength Lifts



USER FLEXIBILITY

- Vehicles can be positioned and lifted symmetrically or asymmetrically
- Power column can be arranged on either the driver or the passenger side
- Vehicle protection with padded overhead shut off
- Overall height can be adjusted 10"

HEAVY-DUTY RESTRAINTS SYSTEM

- Ensures arms remain in set positions
- Three stage front arms provide superior extended and retracted reach
- Screw pads provide 2.5" of adjustment and come standard with removable molded plastic insert (optional height extensions available)



JohnBean™

PRODUCT FEATURES & SPECIFICATIONS

10k Two Post Lift Features

- Light/Medium duty lifting capacity
10,000 lbs (4,536kg)
- Three stage front arms provide versatile vehicle positioning for Symmetric / Asymmetric lifting
- Double telescopic lifting pads with rubber contact surface, adjusts from 4.25" - 6.75" (11-20cm)
- Single piece overhead adds structural strength and ease of installation
- Padded overhead safety shut off bar for improved vehicle protection
- Hi-Rise lifting cylinders and adjustable column height creates maximum under vehicle clearances
- Single point safety lock release system
- Heavy duty replaceable arm restraints ensure engagement
- ANSI/ALI certified to the current lift standard

10k Two Post Lift Optional Accessories



EAK0299T22A

Extension Adapter Kit (includes 3" Stack Extension (4), 6" Stack Extension (2), Organizer Bracket with Mounting Hardware (2))



EAK0299T27A

Air/Electric workstation with filter/lubrication/regulator



EAK0299T23A

6" Stack Adapter Extension (2)



EAK0299T25A*

U-Shaped Frame Truck Adapter (4)



EAK0299T24A

U-Shaped Frame Truck Adapter (2)

Equipment Specifications

- **Capacity: 10,000 lbs (4536kg)**
- **Rise height (Screw pads highest position): 77.75" (200cm)**
- **Overall height (adjustable): 147.5"/137.5" (375-350cm)**
- **Floor to overhead shut off: 140.5"/130.5" (357-331cm)**
- **Overall width: 131.75" (335cm)**
- **Drive thru width: 98.375" (250cm)**
- **Three stage front arm reach: 21.75" to 39.25" (55-100cm)**
- **Rear arm reach: 38.25" to 55.375" (97-141cm)**

Equipment Specifications (Cont.)

- **Lowered pad height: 4.25" to 6.75" (11-20cm)**
- **Width between columns: 110.25" (280cm)**
- **Cylinder height: 148.75" (378cm)**
- **Ceiling height required: 149" (379cm)**
- **Rise time: 52 seconds**
- **Power requirements: 208-240V 1Ph 60Hz**
- **Max load per arm: 2500 lb (1134kg)**

Additional Optional Accessories

- **24" (61cm) Height Extension (Red): EAK0299T40A**
- **Adapter Kit: EAK0299T29A (Includes EAK0299T22A & EAK0299T25A)**

*U-shaped frame truck adapters are required when servicing trucks. Available in kits EAK0299T25A or EAK0299T29A

John Bean is committed to product innovation and improvement. Therefore, specifications and features listed in this brochure may change without notice. ©2015 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.

06/15 SS133318A

For more information regarding the
John Bean 10k Two-Post Automotive Lifts
Call 800.362.4618 (US) or 800.362.4608 (Canada)