

AUTOMOTIVE LIFT SYSTEMS



EELR532A



INDUSTRIAL STRENGTH LIFT SOLUTIONS.
PREMIUM FEATURES.

Unmatched productivity, performance and value.

INTRODUCING THE **10K** AUTOMOTIVE
LIFT SYSTEMS

JohnBean

STANDARD FEATURES

10K Two Post Lift Features

- Vehicles can be positioned and lifted symmetrically or asymmetrically
- Power column can be arranged on either the driver or the passenger side
- Vehicle protection with padded overhead shut off
- Overall height can be adjusted 10" (25.4 cm)
- Ensures arms remain in the set positions
- Three stage front arms provide superior extended and retracted reach
- Screw pads provide 2.5" (6.3 cm) of adjustment and come standard with removable molded plastic insert (optional height extensions available)
- Light/Medium duty lifting capacity of 10,000 lbs (4,536kg)
- Three stage front arms provide versatile vehicle positioning for symmetric / asymmetric lifting
- Double telescopic lifting pads with rubber contact surface, adjusts from 4.25" - 6.75" (11 - 17 cm)
- Single piece overhead adds structural strength and ease of installation
- Padded overhead safety shut off bar for improved vehicle protection
- Hi-Rise lifting cylinders and adjustable column height creates maximum under vehicle clearances
- Single point safety lock release system
- Heavy duty replaceable arm restraints ensure engagement
- Conforms with current ANSI/ALI ALCTV:2011 lift standard

EQUIPMENT SPECIFICATIONS

- Part Number: EELR532A
- Capacity: 10,000 lbs (4,536kg)
- Rise Height (Screw Pads Highest Position): 77.75" (200 cm)
- Overall Adjustable Height: 147.5" / 137.5" (375 / 350 cm)
- Floor to Overhead Shut Off: 140.5" / 130.5" (357 / 331 cm)
- Overall Width: 131.75" (335 cm)
- Drive Thru Width: 98.375" (250 cm)
- Front Arm Reach: 21.75" to 39.25" (55 to 100 cm)
- Rear Arm Reach: 38.25" to 55.375" (97 to 141 cm)
- Lowered Pad Height: 4.25" to 6.75" (11 to 17 cm)
- Ceiling Height Required: 149" (379 cm)
- Inside Column Width: 110.25" (280 cm)
- Rise Time: 52 Seconds
- Maximum Load per Arm: 2,500 lbs (1,134kg)
- Power Requirements: 208-230V 1Ph 60Hz

OPTIONAL ACCESSORIES

- Extension Adapter Kits [Includes Four 3" (7.6 cm) Stack Extensions, Two 6" (15.24 cm) Stack Extensions and Two Organizer Brackets with Mounting Hardware]: EAK0299T22A
- Air/Electric Workstation with Filter/Lubrication/Regulator: EAK0299T27A
- Two 6" (15.24 cm) Stack Adapter Extensions: EAK0299T23A
- Four U-Shaped Frame Truck Adapters: EAK0299T25A*
- Two U-Shaped Frame Truck Adapters: EAK0299T24A*
- 24" (61 cm) Red Column Height Extension Kit; Adds to Vehicle Clearance to Overhead: EAK0299T51A
- Optional Voltages are Available at the Time of Order:
EAK0299T45A: 208V 3Ph
EAK0299T46A: 230V 3Ph

*Frame engaging adapters EAK0299T24A or EAK0299T25A are required when lifting vehicles with frame constructions

For more information regarding the **10k Automotive Lifts** call **800.362.4618 (US)** or **800.362.4608 (Canada)**
www.johnbean.com / www.johnbean.ca

John Bean is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2016 Snap-on Incorporated. All rights reserved. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All other marks are marks of their respective holders.

03/16 SS133318B

JohnBean®