

# 18K 2-POST

Automotive  
Lift System



EELR541A

Shown with optional FRL  
(light and air hose not included)

# JohnBean

# PRODUCT FEATURES & SPECIFICATIONS

## 18k Two Post Lift Features

- Heavy duty lifting capacity 18,000 lbs
- Oversized steel pulley reduces internal stress on equalization cables and provides increased durability
- Medium and high auxiliary adapters and storage brackets come standard
- Single point air actuated safety lock release - allows technician to disengage both columns simultaneously
- Tall 60" lifting carriages balance the long reaching 62" lift arms, optimizing load dispersment in column
- Standard combination stack screw pads accommodate a wide range of manufacturers' recommended vehicle pick up points
- Certified to the ANSI/ALI ALCTV:2011 automotive lift standard

## 18k Two Post Lift Standard Accessories



Organizer Racks for Adapter Storage (2)



U-Shaped Frame Truck Adapter (4)

Standard, Medium and Extended Height Adapters (4)



Reducer Bushings for use with U-Shaped Frame Truck Adapters

## 18k Two Post Lift Specifications

	<b>EELR540A</b>	<b>EELR541A</b>
▪ Capacity:	18,000 lbs (8164kg)	18,000 lbs (8164kg)
▪ Rise height*:	85" (215.9cm)	85" (215.9cm)
▪ Overall height:	174" (442cm)	198" (502.9cm)
▪ Floor to overhead shut off:	167" (424.2cm)	191" (485.1cm)
▪ Overall width:	154.75" (393.1cm)	154.75" (393.1cm)
▪ Drive thru width:	104.25" (264.8cm)	104.25" (264.8cm)
▪ Front and Rear arm reach:	38.5" - 62" (97.8 - 157.5cm)	38.5" - 62" (97.8 - 157.5cm)
▪ Adj. Adapter, Lowered pad height**:	6.625" - 8.5" (16.8 - 21.6cm)	6.625" - 8.5" (16.8 - 21.6cm)
▪ Adj. Adapter, Med Extension**:	10.625" - 12.5" (27 - 31.8cm)	10.625" - 12.5" (27 - 31.8cm)
▪ Adj. Adapter, High Extension**:	14.625" - 16" (36.8 - 40.6cm)	14.625" - 16" (36.8 - 40.6cm)
▪ Width between columns:	119.875" (304.8cm)	119.875" (304.8cm)
▪ Ceiling height requirement:	176" (447cm)	200" (508cm)
▪ Rise time:	60 seconds	60 seconds
▪ Air supply required:	85 - 115 PSI	85 - 115 PSI
▪ Motor:	3 HP	3 HP
▪ Power requirements***:	208-230V 1Ph 60Hz	208-230V 1Ph 60Hz
▪ Max load per arm:	4500 lbs (2041kg)	4500 lbs (2041kg)W

\*Rise height is measured with high extension \*\*Medium and high auxiliary adapter extensions are standard \*\*\*Optional three phase electrical also available, specify at time of order

John Bean is committed to product innovation and improvement. Therefore, specifications and features listed in this brochure may change without notice. ©2015 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 03/15 SS143413A

For more information regarding the 18k 2-Post  
Call 800.362.4618 (US) or 800.362.4608 (Canada)

www.johnbean.com

www.johnbean.ca

# JohnBean