

# 15K 2-POST

Automotive  
Lift System



**JohnBean**

# PRODUCT FEATURES & SPECIFICATIONS

## 15k Two Post Lift Features

- 15,000 lbs of heavy duty lifting power
- Symmetrical lifting with heavy duty arm restraint system
- Single point air actuated safety lock release - allows technician to disengage both columns simultaneously
- Tall 60" lifting carriages balance the long reaching 62" lift arms, optimizing load dispersment in column
- Standard combination stack screw pads accommodate a wide range of manufacturers' recommended vehicle pick up points
- Oversized steel pulley reduces internal stress on equalization cables and provides increased durability
- Padded overhead shut off system prevents vehicle damage from being raised too high
- Certified to the ANSI/ALI ALCTV:2011 automotive lift standard

## 15k Two Post Lift Standard Accessories



Organizer Racks for Adapter Storage (2)



U-Shaped Frame Truck Adapter (4)

Standard, Medium and Extended Height Adapters (4)



Reducer Bushings for use with U-Shaped Frame Truck Adapters

## 15k Two Post Lift Specifications

	<b>EELR538A</b>	<b>EELR539A</b>
▪ Capacity:	15,000 lbs (6804kg)	15,000 lbs (6804g)
▪ Rise height*:	85.5" (217.2cm)	85.5" (217.2cm)
▪ Overall height:	174" (442cm)	198" (502.9cm)
▪ Floor to overhead shut off:	167" (424.2cm)	191" (485.1cm)
▪ Overall width:	154.75" (393.1cm)	154.75" (393.1cm)
▪ Drive thru width:	104.25" (264.8cm)	104.25" (264.8cm)
▪ Front and Rear arm reach:	38.5" - 62" (97.8 - 157.5cm)	38.5" - 62" (97.8 - 157.5cm)
▪ Adj. Adapter, Lowered pad height**:	6.625" - 8.5" (16.8 - 21.6cm)	6.625" - 8.5" (16.8 - 21.6cm)
▪ Adj. Adapter, Med Extension**:	10.625" - 12.5" (27 - 31.8cm)	10.625" - 12.5" (27 - 31.8cm)
▪ Adj. Adapter, High Extension**:	14.625" - 16.5" (37 - 41.9cm)	14.625" - 16.5" (37 - 41.9cm)
▪ Width between columns:	119.875" (304.5cm)	119.875" (304.5cm)
▪ Ceiling height requirement:	176" (447cm)	200" (508cm)
▪ Rise time:	60 seconds	60 seconds
▪ Air supply required:	85 - 115 PSI	85 - 115 PSI
▪ Motor:	2 HP	2 HP
▪ Power requirements***:	208-230V 1Ph 60Hz	208-230V 1Ph 60Hz
▪ Max load per arm:	3750 lbs (1701kg)	3750 lbs (1701kg)

\*Rise height is measured with high extension \*\*Medium and high auxiliary adapter extensions are standard \*\*\*Optional three phase electrical also available, specify at time of order

John Bean is committed to product innovation and improvement. Therefore, specifications and features listed in this brochure may change without notice. ©2014 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 07/14 SS143416

For more information regarding the 15k 2-Post  
Call 800.362.4618 (US) or 800.362.4608 (Canada)

www.johnbean.com

www.johnbean.ca

# JohnBean