



SOET6600

*Starts Low and Uses Less Space!*

**6.6K Double X**

**General-Purpose Scissor Lift**

**JohnBean™**

## Starts Low and Uses Less Space!

New, 6,600 Capacity, Full rise Double Scissor Lift, designed to accommodate a wide range of vehicles. Easy drive over with the extremely low-profile design allows surface mount or flush mount installed. Open center gives free access between the platforms. Starts low, lifts full height and takes up less bay space than other full rise lifts.



SOET6600

## Features

- Space saving full rise scissor lift
- 6,600 lb. capacity
- Low drive over height of 4"
- Lifts straight up - no fore or aft movement
- Open front and rear with no cross member for maximum accessibility
- Double master-slave cylinder system provides synchronization and redundant safety system
- Remote console controls with audible signal control lowering and emergency off function
- Non-slip, textured platform surfaces
- Extendable platform pad, form 60 3/4" to 82 3/4"
- Flush mount installation allows for zero clearance drive over (SOET6600FM)
- 208/230V - 60Hz - 3Ph power option
- Includes a set of four plastic chocks (SOE-VZ975069)

## SPECIFICATIONS

Lifting Capacity	6,600 lbs.
Surface-Mount Max. Lifting Height	74.75"
Flush-Mount Max. Lifting Height	70.5"
Surface-Mount Lowered Height	4.0"
Flush-Mount Lowered Height	0.0"
Lifting Pad Width	21.5"
Overall Width*	74.75"
Adjustable Platform Length	60.75" to 82.75"
Lifting Time (with full load)	46 seconds
Shipping Weight	1,760 lbs.
Power Requirements	208/230V, 1Ph, 60Hz

\*Overall width can be adjusted narrower on installation

## OPTIONAL ACCESSORIES

### Optional Accessories

- Rubber Pads - Flat; 39.37" x 5.9" x 0.78" (4pcs): SOE-VZ975586
- Ductile Plastic Blocks - 3.74" x 5.2" x 13.39" (4pcs): SOE-VZ970045
- Ductile Plastic Blocks - 1.85" x 5.2" x 13.39" (4pcs): SOE-VZ975069
- Hard Rubber Blocks - Connectable (4pcs): SOE-VZ975074
- Aluminum Transverse Beam - Power Coated; 3300 lbs. Capacity Per Beam For Narrow Framed Vehicles: SOE-VZ970127
- Foundation plate included with Flush mount installed version: SOET6600FM

### Optional Accessories

- Long Drive Over Ramps for Low Profile Vehicles - 2 x 52.75" / 2 x 33.07" (4pcs.): SOE-VZ970125
- Extension Set - Hydraulic / Pneumatic Hoses; 39.37" (Max 78.74"): SOE-VZ970052
- Installation Material - 16 Anchors M10 x 130: SOE-VZ999021
- Outrigger Kit - Width extension for wide vehicles - set of 2: SOE-VZ970143