# **6.6K DOUBLE X**

### General Purpose Scissor Lift



Full rise double scissor lift designed to accomodate a wide range of vehicles



## **PRODUCT FEATURES & SPECIFICATIONS**

#### **FEATURES**

- Space saving full rise scissor lift
- 6,600 lb capacity
- Low drive over height of 4"
- Lifts straight up no fore or aft movement
- Open front and rear with no cross member for maximum accessibility
- Double master-slave cylinder system provides synchronization and redundant safety system
- Remote console controls with audible signal control lowering and emergency off function
- Non-slip, textured platform surfaces
- Extendable platform pad, from 60.75" to 82.75"
- Flush mount installation allows for zero clearance drive over (SOET6600FM)
- Includes a set of four plastic blocks (SOE-VZ975069)

#### **OPTIONAL ACCESSORIES**

- Rubber Pads Flat; 39.37" x 5.9" x 0.78" (4pcs): SOE-VZ975586
- Ductile Plastic Blocks 3.74" x 5.2" x 13.39" (4pcs): SOE-VZ970045
- Ductile Plastic Blocks 1.85" x 5.2" 13.39" (4pcs): SOE-VZ975069
- Hard Rubber Blocks Connectable (4pcs): SOE-VZ975074
- Aluminum Transverse Beam Power Coated; 3300 lbs Capacity per Beam for Narrow Framed Vehicles: SOE-VZ970127
- Foundation plate included with Flush Mount Installed Version: SOET6600FM
- Long Drive Over Ramps for Low Profile Vehicles 2 x 52.75" / 2 x 33.07" (4pcs): SOE-VZ970125
- Extension Set Six Hydraulic Hoses, 118" Each and Six Straight Connector Fittings: SOE-VZ970052
- Installation Material 16 Anchors M10 x 130: SOE-VZ999021
- Outrigger Kit Width Extension for Wide Vehicles set of 2: SOE-VZ970143
- 208/230V, 3Ph, 60Hz power option

#### **SPECIFICATIONS**

#### **Equipment Specifications**

- Lifting Capacity: 6,600 lbs
- Surface-Mount Maximum Lifting Height: 74.75"
- Flush-Mount Maximum Lifting Height: 70.5"
- Surface-Mount Lowered Height: 4.0"
- Flush-Mount Lowered
  Height: 0.0"
- Lifting Pad Width: 21.5"
- Overall Width\*: 74.75"
- Adjustable Platform
  Length: 60.75" to 82.75"
- Lifting Time (with full load):
  46 Seconds
- Shipping Weight: 1,760 lbs
- Power Requirements: 208/230V 1Ph 60Hz

\*Overall width can be adjusted narrower on installation

John Bean is committed to product innovation and improvement. Therefore, specifications listed in this brochure may change without notice. © 2014 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 10/14 SS3267A

For more information regarding the 6.6K Double X Call 800.362.4618 (US) or 800.362.4608 (Canada)



www.johnbean.com

www.johnbean.ca