



# 401 & 201

## Brake Lathes

### 401 BRAKE LATHE SPECIFICATIONS

Drive Motor	1HP (1,725 RPM)
Drum/Rotor Carriage Motor	2 Gear Motors
Arbor Speeds	85, 110, 140, 185 (RPM)
Arbor Diameter (Standard)	1"
Maximum Arbor Weight (Standard)	150 lbs.
Rotor/Flywheel Feed Rate Per Revolution	0.001" - 0.010"
Rotor/Flywheel Diameter Range	5" - 30"
Rotor/Flywheel Facing Travel	5"
Rotor Thickness Range	3"
Drum Feed Rate Per Revolution	0.001" - 0.012"
Drum Diameter Range	5" - 30"
Drum Facing Travel	9"
Shipping Weight	525 lbs.
Power Requirements*	120V, 1Ph, 60Hz

### 201 BRAKE LATHE SPECIFICATIONS

Drive Motor	1/2HP (1,725 RPM)
Drum/Rotor Carriage Motor	1 Gear Motors
Arbor Speeds	185 - 195 (RPM)
Arbor Diameter (Standard)	1"
Maximum Arbor Weight (Standard)	150 lbs.
Rotor/Flywheel/Drum Feed Rate Per Rev.	0.0025"
Rotor/Flywheel Diameter Range	5" - 18"
Rotor/Flywheel Facing Travel	4"
Rotor Thickness Range	3"
Drum Diameter Range	5" - 14"
Drum Facing Travel	4"
Shipping Weight	350 lbs.
Power Requirements*	120V, 1Ph, 60Hz

\* Other Power Configurations Available

### OPTIONAL ACCESSORIES



#### Universal Hubless Adapter (20107023)

This universal set offers easier, faster mounting. It can be used for resurfacing both rotors and drums. Fits all brake lathes with a 1" arbor.



#### Heavy-Duty Work Bench (JBC206RED)

Made with 1/2" thick steel and has a built-in chip catcher. Provides over 1' of working space and provides extra room for tooling storage.



#### Backboard (JBC203RED)

Provides extra tooling storage.

For more optional accessories, contact a Local Sales Representative or visit [www.snaponequipment.com](http://www.snaponequipment.com)

Snap-on Equipment / 309 Exchange Avenue / Conway, Arkansas 72032 U.S.A.  
 Fax: 501-450-2085 / Toll Free: 1-800-362-4618 / International: 501-450-1568  
[www.SnaponEquipment.com](http://www.SnaponEquipment.com)

John Bean Canada / 6500 Millcreek Drive / Mississauga, Ontario L5N 2W6  
 Customer Service: 1-800-362-4608 / Fax: 905-826-7800  
[www.johnbean.ca](http://www.johnbean.ca)