

PRODUCT FEATURES & SPECIFICATIONS



Equipment Specifications*

EHP System V

EHP System IV-E

EHP System III-E

EHP System II-E

▪ Part Number:	EEWH517B	EEWH514BE	EEWH513BU1	EEWH512AE
▪ Two-speed part number:	EEWH554A	EEWH553AE	N/A	N/A
▪ Outer-clamping diameter range:	12" - 26"	10" - 24"	10" - 24"	10" - 24"
▪ Inner-clamping diameter range:	14" - 26"	12" - 24"	12" - 24"	12" - 24"
▪ Maximum wheel width:	16"	15"	15"	12"
▪ Maximum tire diameter:	47"	40"	50"***	40"
▪ Compressed air supply:	110-170 PSI	110-170 PSI	110-170 PSI	110-170 PSI
▪ Adjustable 4-claw wheel clamp:	Included	Included	Included	Included
▪ Integrated bead-seating jets:	Included	Included	Included	Included
▪ Pressure timer:	Included	Included	Included	Included
▪ Twin cylinder turntable clamping:	Included	Included	Included	Included
▪ Bead breaker power:	3,400 lbs @ 170 PSI	3,400 lbs @ 170 PSI	3,400 lbs @ 170 PSI	3,400 lbs @ 170PSI
▪ Bead breaker range:	Position One: 2.5" - 12" Position Two: 6" - 16.5"	Single 3" - 16"	Single 2" - 18"	Single 3" - 13"
▪ Recommended floor space:	72" (W) x 78" (D)	72" (W) x 78" (D)	67" (W) x 69" (D)	62" (W) x 70" (D)
▪ Shipping weight:	1,000 lbs	960 lbs	805 lbs	530 lbs
▪ Power requirements:	120V 1Ph 60Hz	120V 1Ph 60Hz	120V 1Ph 60Hz	120V 1Ph 60Hz
▪ Two-speed power requirements:	208-230V 1Ph 16A 60Hz	208-230V 1Ph 16A 60Hz	N/A	N/A
▪ Two-speed revolution speed:	7/14 CW & 7 CCW	7/14 CW & 7 CCW	N/A	N/A
▪ Optional Pneumatic Bead Assist Part #:	Standard	EAA0329G34B	EAA0329G33B	EAA0329G33B

*Specifications based on OEM tires
**42" diameter when PBA is installed



John Bean is committed to product innovation and improvement. Therefore, specifications listed in this brochure may change without notice. © 2014 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.

03/14 SS2561M

For more information regarding the
EHP Series Tire Changers
Call 800.362.4618 (US) or 800.362.4608 (Canada)